

HERMLE

Benchmark

Z216 Series

Z216-M

Z216-MK

Microcentrifuges

- Unique 44 place micro rotor
- High speed, up to 21,379 x g
- Available with refrigeration
- 11 rotor options for microtubes, PCR strips and 5ml tubes



Z216-M Microcentrifuge



Z216-MK Microcentrifuge

HERMLE  Z 216 M
Benchmark

Z216 Series Summary

Speed up to 15,000 rpm
G-Force up to 21,631 x g

Angle Rotor Capacity
44 x 1.5/2.0 ml
4 x PCR Strips
60 x 0.5 ml
12 x 5 ml

Z216 Features

Microprocessor Control

- Over-speed protection
- Program Storage (99)
- Pre-Cool function (Z216-K only)
- Momentary spin button
- Imbalance detection
- Adjustable Accel/Decel
- Audible end of run alarm

Maintenance free induction drive

- Motor driven safety lid-lock
- Quiet operation, less than 60 DB
- Splash proof display

Powerful Refrigeration (Z216-K only)

(Room temp to 4°C in less than 10 min.)

Z216 Specifications

Speed Range: 200 to 15,000 rpm
Max. RCF: 21,631 x g
Max Capacity: 44 x 1.5/2.0 ml
Timer: up to 99 hr, 59 min.
Dimensions: 11 x 15.3 x 11.4 in.
(W x D x H) 28 x 39 x 29 cm.
Z216-MK 11 x 21.6 x 11.4 in.
28 x 55 x 29 cm.
Weight: 37.4 lbs (17 kg)
Z216-MK 77 lbs (35 kg)
Electrical: 120 or 230V, 50/60Hz
Power Draw: 280W (Z216-MK: 560W)

Temp Range: -20° - 40° C
(Z216-MK only)

Compact, quiet, and powerful are just a few of the features found on the Z216 series microcentrifuges. Add to this, the versatility of eleven available rotor options, and the result is the ideal microcentrifuge for the modern molecular biology laboratory.

All common microtubes (0.2ml, 0.5ml, 1.5ml, 2.0ml) can be accepted as well as PCR strips, hematocrit tubes, and even 5.0ml centrifuge tubes. Advanced microprocessor controls allow for setting/displaying of the rotational speed in either rpm or rcf. In addition to retrieving saved programs, the easy to use front panel can adjust accel/decel rates, and change the end of run alarm tone.

Despite a remarkably small footprint, the Z216 series offers a uniquely designed 44 x 1.5ml dual row rotor, nearly doubling the capacity when compared to traditional microcentrifuges. Select rotors also feature our convenient Quick-Seal™ lid which locks with just a quarter turn.

In the Z216-MK model a powerful, compressor driven cooling system maintains temperatures as low as -20°C and is designed to reach 4°C (from room temperature) in less than 10 minutes.

Z216-M* Centrifuge (without rotor), 120V
Z216-MK* Z216-MK Refrigerated Centrifuge (without rotor), 120V
*115V with US Plug. For 230V (EU Plug), please order -E.



Item: Z216-2420
24 x 1.5/2.0ml Angle Rotor w/
Quick-Seal lid (45°)
Max Speed: 15,000 rpm / 21,379 x g
Accel: 21 sec. / Decel: 18 sec.



Item: Z216-4420
44 x 1.5/2.0ml Angle Rotor w/
Quick-Seal lid (32°/55°)
Max Speed: 15,000 rpm / 21,379 x g
Accel: 25 sec. / Decel: 17 sec.



Item: Z216-2420S
24 x 1.5/2.0ml + 4 x PCR
COMBI-rotor w/ Quick-Seal lid (45°)
Max Speed: 15,000 rpm / 21,631 x g
Accel: 28 sec. / Decel: 27 sec.



Item: Z216-2420H
24 x 1.5/2.0ml Angle Rotor (45°)
Hermetically Sealed Lid
Max Speed: 15,000 rpm / 21,379 x g
Accel: 21 sec. / Decel: 21 sec.



Item: Z216-3020H
30 x 1.5/2.0ml Angle Rotor (45°)
Hermetically Sealed Lid
Max Speed: 13,500 rpm / 19,151 x g
Accel: 29 sec. / Decel: 27 sec.



Item: Z216-6005
60 x 0.5ml Angle Rotor (40°/55°)
Max Speed: 13,500 rpm / 16,298 x g*
Accel: 16 sec. / Decel: 17 sec.

*14,261 (inner row)



Item: Z216-3202
4 x 8 PCR Strips / 32 x 0.2ml (45°)
Hermetically Sealed
Max Speed: 15,000 rpm / 15,343 x g
Accel: 17 sec. / Decel: 16 sec.



Item: Z216-1205
12 x 5ml (45°)
Hermetically Sealed
Max Speed: 14,500 rpm / 19,978 x g
Accel: 24 sec. / Decel: 17 sec.



Item: Z216-24HEM
24 x Capillaries (90°)
Z216-M ONLY
Max Speed: 12,000 rpm / 14,970 x g
Accel: 15 sec. / Decel: 15 sec.



Item: Z216-24SC
24 x 2.0ml Spin Column Kits w/
Quick-Seal lid (45°)
Max Speed: 9,000 rpm / 7,510 x g
Accel: 21 sec. / Decel: 18 sec.

Inserts/Adapters
Z216-05-C10: 1.0ml Cryo
Z216-05-C18: 1.8ml Cryo



Item: Z216-1220H
12 x 1.5/2.0ml Swing out rotor (90°)
Max Speed: 9,000 rpm / 7,510 x g
Accel: 5 sec. / Decel: 5 sec.